






Jännite	Napaluku	Virta A	Tuote		IP	Koko (mm)	Kytkin Krausneimer/ BG	Apukosketin On
			Laji	SSTL				
 230V	Suko	16	768	24 290 05	IP54			
	3	16	1619	24 298 07	IP44	170x90		
	3	16	160048	24 298 10	IP67	170x90		
 400V	4	16	1610	24 287 60	IP44	170x90	BG	
	4	16	16276	24 287 46	IP44	170x90		X
	4	16	160049	24 287 47	IP67	170x90	BG	
	4	32	16042	24 287 48	IP44	225x118	KN	
	4	32	16531	24 287 49	IP44	225x118		X
	4	32	160178	24 287 50	IP67	225x118		
	4	63	16605	24 287 62	IP44	260x160	KN	
	4	63	160285	24 287 51	IP44	260x160	KN	X
	4	63	16604	24 287 52	IP67	260x160	KN	
4	125	16621	24 287 53	IP67	460x160	KN		
 400V	5	16	1611	24 298 09	IP44	170x90	BG	
	5	16	16870	24 298 02	IP44	170x90		X
	5	16	160052	24 298 03	IP67	170x90		
	5	32	16043	24 298 13	IP44	225x118	KN	
	5	32	16333	24 298 04	IP44	225x118		X
	5	32	160177	24 298 05	IP67	225x118		
	5	63	16603	24 298 22	IP44	260x160	KN	
	5	63	160279	24 298 23	IP44	260x160		X
	5	63	16602	24 298 25	IP67	260x160		
5	125	16622	24298 26	IP67	460x160			
 500V	4	16	1616	24 298 32	IP44	170x90		
	4	16	160057	24 298 33	IP67	170x90		
	4	32	16066	24 287 67	IP67	170x90		
	4	32	16685	24 298 36	IP44	225x118		X
	4	32	160179	24 298 37	IP67	225x118		
	4	63	16827	24 298 68	IP44	225x118		
	4	63	16828	24 298 69	IP67	260x160		
4	125	16831	24 298 70	IP67	460x160			
 690V	4	16	16134	24 299 30	IP67	170x90		
	5	16	16083	24 299 14	IP67	170x90		
	4	32	16133	24 299 31	IP67	225x118		
	5	32	16465	24 299 15	IP67	225x118		
	4	63	16959	24 299 32	IP67	260x160		

- Pistotulppa voidaan poistaa rasiasta vain kytkimen 0-asennossa.
- Varustettu mekaanisella lukituksella.
- Mahdollisuus lukita lisäksi maksimissaan kolmella erillisellä lukolla 0- tai I-asennossa.

KN = Tuotteeseen on saatavilla jälkiasenteisena apukosketin. Laji H010/11A-VE